

We bring your ideas to life! Brake roller for roller conveyors

As a system supplier, we are your partner all the way from consulting and development through to sampling of high-quality plastic parts - from individual items to large-scale series production. You can expect the right solution from us, because if required, we assemble complex components into ready-to-install assemblies.

With our development department as well as our own technical center and toolmaking facilities, we proactively meet these demands of our customers. Because high-quality products at fair prices and on-time delivery - this is what our customers have valued for many years.

Alongside price and quality, the market launch date is the most important criterion for the success of a new product.



load in kg	2° incline Roller conveyor	3° incline Roller conveyor	4° incline Roller conveyor
100	BTR 100 L	BTR 100 L	BTR 100 L
200	BTR 200 L	BTR 200 L	BTR 200 L
300	BTR 200 L	BTR 200 L	BTR 200 L + R
400	BTR 500 L	BTR 500 L	BTR 500 L
500	BTR 500 L	BTR 500 L	BTR 500 L
600	BTR 500 L	BTR 500 L	BTR 500 L + R
700	BTR 500 L	BTR 800 L	BTR 800 L
800	BTR 800 L	BTR 800 L	BTR 800 L + R
900	BTR 800 L	BTR 800 L	BTR 800 L + R
1000	BTR 1200 L	BTR 1200 L	BTR 1200 L
1100	BTR 1200 L	BTR 1200 L	BTR 1200 L + R
1200	BTR 1200 L	BTR 1200 L	BTR 1200 L + R

Conveyed material speed: 0.20-0.35 m/s

BTR xxx L: Brake support roller on one side - support bearing on one side

BTR xxx L + R: Brake support roller on both sides

Packaging unit: 24 pcs./PU

Support bearing: 48 pcs./PU

For steel tube: according to DIN 2448, seamless, dimensions: 88.9 mm x 2.6 mm

BTR 800 L | 800 kg | 3°

